TC-DIAU-2C

2ch Dante In to Line Out Converter

Two Dante channels back to analogue line level


2 ch	24-bit	+18 dBu	PoE
analogue line out · balanced or unbalanced	PCM 2.0 at 44.1 / 48 / 96 kHz	the highest of three GAIN settings · 0 dBu default · −10 dBV	802.3af Class 0 · or 12 V DC

TC-DIAU-2C takes two channels from the Dante network and delivers them as analogue line level, balanced or unbalanced, on a 6-pin 3.81 mm Phoenix connector — to an amplifier or any other line-level input. A three-position GAIN switch sets the level for the input it feeds — +18 dBu, 0 dBu (the default) or −10 dBV — and it receives PCM at 44.1, 48 or 96 kHz, up to 24-bit, on Dante, with AES67 (RTP) support.

One RJ45 port carries the audio and the power: the converter draws 1.32 W, from PoE (IEEE 802.3af, Class 0) or from a 12 V DC supply on a 2-pin Phoenix connector; no adapter is supplied. It runs at 100 Mbps over up to 100 m of CAT6/6A to the switch and is set up in Dante Controller. The black metal case measures 120 × 47 × 26 mm.

01 KEY CAPABILITIES

- Two line-level channels out of the Dante network, balanced or unbalanced
- Powered over the network cable (PoE, 802.3af Class 0), or from a 12 V DC supply
- Dante, with AES67 RTP audio transmission
- LINK and DATA LEDs on the Dante port



SIGNAL PATH · TWO DANTE CHANNELS OUT TO LINE LEVEL, POWERED OVER THE NETWORK CABLE

02 AUDIO

Analogue audio output	2-channel line output, balanced or unbalanced (6-pin 3.81 mm Phoenix)
Networked audio	Dante · AES67 RTP
Gain	Output level, on a 3-position GAIN switch: +18 dBu, 0 dBu (default) or −10 dBV
Other audio formats	PCM 2.0 · 44.1 / 48 / 96 kHz · up to 24-bit

03 TRANSPORT & DISTANCE

Network	100 Mbps
Transmission distance	100 m (CAT6/6A)
Power over the link	PoE, IEEE 802.3af Class 0

04 CONNECTIVITY

Network ports	1 × RJ45 Dante (PoE)
Other ports	DC 12 V in (2-pin 3.81 mm Phoenix)

05 CONTROL

Control methods	Dante Controller

06 ELECTRICAL & PHYSICAL

Power supply	PoE, IEEE 802.3af Class 0 — no adapter supplied (a 12 V DC input, 2-pin Phoenix, is also fitted)
Power consumption	1.32 W
Dimensions (W × D × H)	120 × 47 × 26 mm
Weight	186 g
Housing	Metal, black
Operating temperature	0 to 40 °C
Storage temperature	−20 to 60 °C
Humidity	20–90 % RH, non-condensing

07 COMPLIANCE & ASSURANCE

Certification statement	Designed for global compliance — CE, FCC, RoHS, and regional certifications, as applicable.
Warranty	3 years

08 IN THE BOX

In the box	Converter · 6-pin and 2-pin 3.81 mm Phoenix connectors

09 ORDERING

Order code	**TC-DIAU-2C**

PRODUCT PAGE

telecis.com/products/pro-audio/tc-diau-2c/

Specifications are subject to change without notice. Dante is a registered trademark of Audinate Pty Ltd. Other product names, brand names, and trademarks referenced are the property of their respective owners. Reference to such marks does not imply endorsement or affiliation.

signal · engineered.